

TECHNICAL DATA SHEET



SYNTHETIC SAE 0W-30 RACING ONLY

PRODUCT # 10605, 10606, 10607,
10608, 10609

TEST

ASTM

TYPICAL

| | | |
|---------------------------|--------|------------------|
| API Gravity | D-1298 | 33.2 |
| Specific Gravity @ 60°F | D-1298 | 0.859 |
| Density @ 60°F LBS/US Gal | D-1298 | 7.16 |
| Viscosity @ 40°C, cSt | D-445 | 63.6 |
| Viscosity @ 100°C, cSt | D-445 | 11.3 |
| Flash Point COC °F | D-92 | 445 |
| Color | | Amber |
| Viscosity Index | D-2270 | 168 |
| CCS @ -35°C, CPS | D-5293 | 6,200 Max |
| MRV @ -40°C, CPS | D-4684 | 60,000 Max |
| Zinc, Wt % | X-Ray | 3000 PPM Typical |

Lucas Synthetic SAE 0W-30 Racing Oil is made with the highest quality synthetic base oils and is fortified with a unique additive package containing high levels of zinc, molybdenum and phosphorus, which provides a tougher, thicker additive film for maximum protection even under the most severe conditions. It lowers oil temperatures, extends oil life and minimizes metal fatigue. It has excellent cold temperature properties and stands up to high operating temperatures.

Lucas Synthetic SAE 0W-30 Racing Oil is typically used in NASCAR, Late Model, Super Late Model, ARCA, Modifieds, Sprint Cars, Midgets, IRL, NHRA, Stock, Super Stock, Comp and Super Comp. Excellent for use with turbo charged engines.

Lucas Synthetic SAE 0W-30 is for RACING APPLICATIONS ONLY. It is not recommended for passenger car use.