

## PRODUCT SPECIFICATION SHEET



# 30 wt. PLUS

**PRODUCT #10053**

**API Service SM/SL/SJ/CF**

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>27.9</b>
<b>Specific Gravity @ 60° F</b>	<b>D-1298</b>	<b>.8877</b>
<b>Density @ 60° F LBS/US Gal</b>	<b>D-1298</b>	<b>7.392</b>
<b>Viscosity @ 40° C cSt</b>	<b>D-445</b>	<b>94</b>
<b>Viscosity @ 100° C cSt</b>	<b>D-445</b>	<b>11.0</b>
<b>VI</b>		<b>109</b>
<b>Flash Point COC °F</b>	<b>D-92</b>	<b>440°</b>
<b>Color</b>		<b>Amber</b>

**Lucas 30 wt. Plus is a blend of high quality base stocks and an exclusive additive package that sets it far apart from other 30 wt. oils.**

**Lucas 30 wt. Plus is designed to lower oil temperature and slow oil consumption. Lucas 30 wt. Plus extends the life of engines in race cars, lawn equipment, farm equipment or any other situation where a superior 30 wt. oil is needed.**

**Excellent for use in light duty manual transmissions and hydro stat transmissions.**

**Meets or exceeds all manufacturers specifications.**