

PRODUCT SPECIFICATION SHEET



SYNTHETIC 5W-40

PRODUCT #10186, 10189

TEST

ASTM

TYPICAL

API Gravity	D-1298	32.6
Specific Gravity @ 60° F	D-1298	.8623
Density @ 60° F LBS/US Gal	D-1298	7.180
Viscosity @ 40° C cSt	D-445	71
Viscosity @ 100° C cSt	D-445	13.5
VI		189
Flash Point COC °F	D-92	430°
Color		Light Brown

Lucas Synthetic 5W-40 motor oil is a formulation of high quality synthetic base stocks and an exclusive high performance additive package. It's an ideal on track/off track lubricant that ensures minimum drag for maximum fuel mileage, and easy cold weather starting. The user can expect maximum protection from wear even with extended drain intervals.

The exclusive additive package in Lucas Synthetic 5W-40 ensures extra protection and longer oil life in turbo charged engines. The user can expect lower oil temperatures and more miles/kilometers between overhauls.

Designed for use in both gasoline and diesel engines.

**Meets or exceeds all manufacturers specifications for SAE5W-40 and APISL and ILSACGF3. Exceeds A3/B3/B4 • SJ/CF/CC.
Exceeds VW 505.01 - 505.00 - 500.00 and Ford WSS M2 C 917 A.**