

## PRODUCT SPECIFICATION SHEET



# SEMI-SYNTHETIC 10W-40

PRODUCT #10172,10176

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>32.1</b>
<b>Specific Gravity @ 60° F</b>	<b>D-1298</b>	<b>.8649</b>
<b>Density @ 60° F LBS/US Gal</b>	<b>D-1298</b>	<b>7.202</b>
<b>Viscosity @ 40° C cSt</b>	<b>D-445</b>	<b>97</b>
<b>Viscosity @ 100° C cSt</b>	<b>D-445</b>	<b>15.0</b>
<b>VI</b>		<b>170</b>
<b>Flash Point COC °F</b>	<b>D-92</b>	<b>380°</b>
<b>Color</b>		<b>Amber</b>

**Lucas Semi Synthetic 10W-40 is a blend of high quality base stocks and an exclusive high performance additive package that ensures minimum drag, extended engine life, longer oil life and easy cold weather starting.**

**Designed for use in both gasoline and diesel engines.**

**The exclusive additive package in Lucas Semi Synthetic 10W-40 allows for extended drain periods.**

**Lucas Semi Synthetic 10W-40 is excellent for use in turbo charged engines. The user can expect longer oil life and lower oil temperature.**

**Meets or exceeds all manufacturers specifications for A3/B3/B4 • SM/SL/SJ/CF. Exceeds VW 505.01 - 505.00 - 500.00 and Ford WSS M2 C 917 A.**