

PRODUCT SPECIFICATION SHEET



SYNTHETIC 20W-50

PRODUCT # 10054, 10060, 10108, 10109, 10135

API Service SM/SL/SJ/CF

TEST

ASTM

TYPICAL

| | | |
|----------------------------------|---------------|--------------|
| API Gravity | D-1298 | 27.2 |
| Specific Gravity @ 60°F | D-1298 | .8916 |
| Density @ 60°F LBS/US Gal | D-1298 | 7.424 |
| Viscosity @ 40°C | D-445 | 111.5 |
| Viscosity @ 100°C | D-445 | 18 |
| Flash Point COC °F | D-92 | 425° |
| Color | | Amber |

This excellent product provides the consistent viscosity needed for precision ET racing. It also stands up to heat and fuel dilution for the longevity required by circle track and off-road racers. LUCAS Synthetic 20W-50 is a formulation of only the finest light synthetic base oils plus an exclusive additive package that includes lubricity agents and anti-seize agents that control drag like a zero weight oil and protect like a heavy multi-viscosity oil.

It's the perfect non-foaming lubricant for high RPM performance engines, including motorcycle engines.

It's also excellent for normal highway use.

Lucas Synthetic 20W-50 is the perfect lubricant for low temperatures or extreme high temperatures and blends with other synthetic or regular motor oil. Blend a quart or two into your conventional motor oil for easier starting and longer oil life.

Meets or exceeds all manufacturers specifications for SAE20W-50 and APISL and ILSACGF3. Exceeds A3/B3/B4 • SM/SL/SJ/CF.