

Section 1 - Identification of The Material and Supplier		
Lucas Oil Products of Australia Pty Ltd Unit 2/5-7 Meakin Rd Meadowbrook, Qld 4131		Phone: 07 3299 6320 (office hours Phone 0407 751 175 (24/7 Fax: 07 3299 736
Chemical nature:	Gasoline treatment	
Trade Name:	Lucas Diesel Deep Clean	
Product Code:	10872, 10873	
Product Use:	Gasoline treatment	
Creation Date:	August, 2016	
This version issued: Poisons Information Ce	August, 2016 and is valid for 5 ntre: Phone 13 1126 from anyw	-

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xn, Harmful. Xi, Irritating. N, Dangerous to the environment. Hazardous according to the criteria of SWA.

Not subject to the ADG Code when transported in Australia by Road or Rail in packages 500kg (L) or less; or IBCs (refer to SP AU01). However if transported by Air or Sea, this provision does not apply. Then the product is classed as Dangerous (Class 9 Environmentally Hazardous) by IATA and IMDG/IMSBC respectively. See details below and in Section 14 of this SDS.

SUSMP Classification: S5

ADG Classification: Class 9: Miscellaneous Dangerous Goods.

UN Number: 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.



$\langle \cdot \rangle$



GHS Signal word: DANGER

Flammable liquids Category 4 Aspiration Hazard Category 1 Skin Corrosion /Irritation Category 2 Serious eye damage/eye irritation Category 2/2A Specific Target Organ toxicity - repeated exposure Category 1 Hazardous to aquatic environment Short term/Chronic Category 1

HAZARD STATEMENT:

- H227: Combustible liquid.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H331: Toxic if inhaled.

H372: Causes damage to organs through prolonged or repeated exposure.

H410: Very toxic to aquatic life with long lasting effects.

PREVENTION

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P235: Keep cool.

P260: Do not breathe fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P273: Avoid release to the environment.

P280: Wear protective gloves, protective clothing and eye or face protection.

SAFETY DATA SHEET

Issued by: Lucas Oil Products of Australia Pty Ltd

Phone: 07 3299 6320 (office hours)



RESPONSE

P314: Get medical advice or attention if you feel unwell.

P331: Do NOT induce vomiting.

P362: Take off contaminated clothing and wash before reuse.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P391: Collect spillage.

STORAGE

P405: Store locked up.

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Clear straw-coloured liquid.

Odour: Petroleum solvent odour.

Major Health Hazards: may cause serious damage to eyes, skin irritant, if aspirated, may cause lung damage.

Section 3 - Composition/Information on Ingredients

Section 5 - Composition/mormation on ingredients				
Ingredients	CAS No	Conc, %	TWA (mg/m ³)	STEL (mg/m ³)
Liquid hydrocarbon	64742-88-7	50-75	not set	not set
Oxirane, 2-ethyl-, homopolymer, 3-aminopropyl C ₁₁₋₁₄ -isoalkyl ethers, C ₁₃ -rich				
	secret	25-50	not set	not set
Alkyl ether carboxylic acid	secret	1-3	not set	not set
Amines, tallow alkyl, ethoxylated	61791-26-2	0.3-1	not set	not set
Amines, tallow alkyl	61790-33-8	0.01-0.1	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set
			• • •	e

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Skin Contact: Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

SAFETY DATA SHEET

Issued by: Lucas Oil Products of Australia Pty Ltd

Phone: 07 3299 6320 (office hours)



Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a risk of an explosion from this product if commercial quantities are involved in a fire. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures. **Extinguishing Media:** In case of fire, use carbon dioxide, dry chemical, foam. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses. Avoid the use of water jet or water-based fire extinguishers.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is little danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus. Cool closed, undamaged containers exposed to fire with water spray.

Flash point:	68°C (Pensky Martin closed cup) ASTM D 93
Upper Flammability Limit:	No data.
Lower Flammability Limit:	No data.
Autoignition temperature:	No data.
Flammability Class:	Flammable Category 4 (GHS), C1 combustible (AS 1940)

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include no specific manufacturer recommendations. Use impermeable gloves with care. Eye/face protective equipment should comprise, as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Because of the environmentally hazardous nature of this product, special care should be taken to restrict release to waterways or drains. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**. Exposure limits have not been established by SWA for any of the known significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

SAFETY DATA SHEET

Issued by: Lucas Oil Products of Australia Pty Ltd

Phone: 07 3299 6320 (office hours)



Ventilation: This product should only be used where there is ventilation that is adequate to keep exposure below the TWA levels. If necessary, use a fan.

Eye Protection: Protective glasses or goggles must be worn when this product is being used. Failure to protect your eyes may lead to severe harm to them or to general health. Emergency eye wash facilities must also be available in an area close to where this product is being used.

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

Protective Material Types: There is no data that enables us to recommend any type except that it should be impermeable.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section	9 - Ph	vsical and	l Chemical	Properties:
---------	--------	------------	------------	--------------------

Physical Description & colour:	Clear straw-coloured liquid.
Odour:	Petroleum solvent odour.
Boiling Point:	179°C at 100kPa
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	No data.
Vapour Pressure:	No data.
Vapour Density:	No data.
Specific Gravity:	0.8658
Water Solubility:	Negligible.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data
Viscosity:	Kinematic: 0.038 cm ² /s (3.8 cSt) at 100°C
Autoignition temp:	No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Protect this product from light.

Incompatibilities: oxidising agents.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: Polymerisation reactions are unlikely; they are not expected to occur.

Section 11 - Toxicological Information

Toxicity: A summary of white spirit type hydrocarbons can be found at

http://www.inchem.org/documents/ehc/ehc/ehc187.htm

Ingestion of white spirit has been reported to produce gastrointestinal irritation with pain, vomiting and diarrhoea. Lesions of the mucous membranes in the oesophagus and the gastrointestinal tract followed the oral exposure. Owing to its low viscosity and low surface tension, white spirit poses a risk of aspiration into the lungs following oral exposure. A few mL of solvent aspirated into the lungs are able to produce serious bronchopneumonia and 10-30mL may be fatal.

SAFETY DATA SHEET

Issued by: Lucas Oil Products of Australia Pty Ltd Phone: 07 3299 6320 (office hours)



Prolonged dermal exposure to white spirit, e.g., resulting from wearing clothes that have been soaked or moistened by white spirit for hours, may produce irritation and dermatitis.

Single cases of acute toxicity to the kidney, liver and bone marrow have been reported following exposure to white spirit at high levels. However, owing to lack of details and the sporadic nature of the reports, the relevance of these findings is unclear.

Inhalation of aliphatic hydrocarbon vapours seems to show little toxicity but, these vapours are CNS depressants and have a disinhibiting euphoric effect.

Potential Health Effects

Inhalation:

Short Term Exposure: Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort. **Long Term Exposure:** No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is a severe eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms such as swelling of eyelids and blurred vision may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment is likely to cause permanent damage.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. Ingestion of this product may cause nausea and vomiting. This product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

Section 12 - Ecological Information

Very toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment.

Environmental toxicity for amines, tallow alkyl, ethoxylated: Acute LC_{50} is 2.6 µg/L for *Thamnocephalus platyurus*, 2350 µg/L for *Daphnia pulex* and 650 µg/L for *Oncorhyncus mykiss*.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

Section 14 - Transport Information

Not subject to the ADG Code when transported by Road or Rail in Australia, in packages 500kg (L) or less; or IBCs, but classed as Dangerous by IATA and IMDG/IMSBC when carried by Air or Sea transport (see details below).

UN Number: 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Hazchem Code: •3Z Special Provisions: 179, 274, 331, 335, AU01 Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

SAFETY DATA SHEET

Issued by: Lucas Oil Products of Australia Pty Ltd

Phone: 07 3299 6320 (office hours)



Dangerous Goods Class: Class 9: Miscellaneous Dangerous Goods. Packing Group: III Packing Instruction: P001, IBC03, LP01

Class 9 Miscellaneous Dangerous Goods shall not be loaded in the same vehicle or packed in the same freight container with Dangerous Goods of Class 1 (Explosives).

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:	
ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number
TO SAFELY HANDLE AND USE	BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW E THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW DLED AND USED IN THE WORKPLACE.
	ER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, T THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS
	RODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)

Copyright © Kilford & Kilford Pty Ltd, August, 2016.

http://www.kilford.com.au/ Phone (02)9251 4532