

Page: 1 of 6

This version issued: August, 2016

Phone 0407 751 175 (24/7)

Fax: 07 3299 7365

Section 1 - Identification of The Material and Supplier

Lucas Oil Products of Australia Pty Ltd Phone: 07 3299 6320 (office hours)

Unit 2/5-7 Meakin Rd Meadowbrook, Qld 4131

Chemical nature: Fuel additive.

Trade Name: Lucas Fuel Stabilizer

Product Code: 10302, 10303, 10324, 10325, 10326

Product Use: Fuel additive.

Creation Date: August, 2016

This version issued: August, 2016 and is valid for 5 years from this date. Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xn, Harmful. Xi, Irritating. Hazardous according to the criteria of SWA.

Not a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA or IMDG/IMSBC criteria.

SUSMP Classification: S5

ADG Classification: None allocated. Not a Dangerous Good according to Australian Dangerous Goods (ADG)

Code, IATA or IMDG/IMSBC criteria. **UN Number:** None allocated



GHS Signal word: DANGER

Flammable liquids Category 4

Aspiration Hazard Category 1

Skin Corrosion /Irritation Category 2

Acute Toxicity Inhalation Category 4

Specific Target Organ Toxicity - Single Exposure Category 3

HAZARD STATEMENT:

H227: Combustible liquid.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

PREVENTION

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P261: Avoid breathing fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P271: Use only outdoors or in a well ventilated area.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P362: Take off contaminated clothing and wash before reuse.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTRE or doctor. P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

SAFETY DATA SHEET

Issued by: Lucas Oil Products of Australia Pty Ltd Phone: 07 3299 6320 (office hours)



Page: 2 of 6

This version issued: August, 2016

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P332+P313: If skin irritation occurs: Get medical advice.

P370+P378: In case of fire, use carbon dioxide, dry chemical or foam.

STORAGE

P405: Store locked up.

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Clear bright blue liquid.

Odour: Petroleum odour.

Major Health Hazards: harmful if inhaled, skin irritant, if aspirated, may cause lung damage.

Section 3 - Composition/Information on Ingredients				
Ingredients	CAS No	Conc, %	TWA (mg/m ³)	STEL (mg/m ³)
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	30-60	not set	not set
Solvent naphtha (petroleum), light arom.	64742-95-6	1-5	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: If symptoms of poisoning become evident, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

Eye Contact: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam. Avoid the use of water jet or water-based fire extinguishers.

Fire Fighting: When fighting fires involving significant quantities of this product, wear a fully encapsulated splash suit complete with self contained breathing apparatus.

Flash point: 88°C Upper Flammability Limit: No data.

SAFETY DATA SHEET

Issued by: Lucas Oil Products of Australia Pty Ltd Phone: 07 3299 6320 (office hours)



Page: 3 of 6

This version issued: August, 2016

Lower Flammability Limit: No data. **Autoignition temperature:** No data.

Flammability Class: Flammable Category 4 (GHS), C1 combustible (AS 1940)

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include no specific manufacturer recommendations. Use impermeable gloves with care. Eye/face protective equipment should comprise, as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Note that this product is GHS Flammable Class 4 and therefore, for Storage, meets the definition of Dangerous Goods. If you store large quantities (tonnes) of such products, we suggest that you consult your state's Dangerous Goods authority in order to clarify your obligations regarding their storage.

Store packages of this product in a cool place. Make sure that containers of this product are kept tightly closed. Keep containers dry and away from water. Keep containers of this product in a well ventilated area. Keep away from sources of ignition such as sparks and open flames. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Some liquid preparations settle or separate on standing and may require stirring before use. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**. Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems. **Ventilation:** This product should only be used where there is ventilation that is adequate to keep exposure below the TWA levels. If necessary, use a fan.

Eye Protection: Eye protection is not normally necessary when this product is being used. However, if in doubt, wear suitable protective glasses or goggles.

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product.

Protective Material Types: There is no data that enables us to recommend any type except that it should be impermeable.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.



Page: 4 of 6

This version issued: August, 2016

Section 9 - Physical and Chemical Properties:

Physical Description & colour: Clear bright blue liquid.
Odour: Petroleum odour.
Boiling Point: 191-211°C at 100kPa

Freezing/Melting Point: No specific data. Liquid at normal temperatures. **Volatiles:** No specific data. Expected to be low at 100°C.

Vapour Pressure: No data. **Vapour Density:** No data. **Specific Gravity:** 0.8514 Water Solubility: Negligible. :Ha No data. Volatility: No data. **Odour Threshold:** No data. **Evaporation Rate:** No data. Coeff Oil/water Distribution: No data

Viscosity: Kinematic: 0.035 cm²/s (3.5 cSt) at 100°C

Autoignition temp: No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition.

Incompatibilities: oxidising agents.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: Polymerisation reactions are unlikely; they are not expected to occur.

Section 11 - Toxicological Information

Toxicity: A summary of white spirit type hydrocarbons can be found at

http://www.inchem.org/documents/ehc/ehc/ehc187.htm

Ingestion of white spirit has been reported to produce gastrointestinal irritation with pain, vomiting and diarrhoea. Lesions of the mucous membranes in the oesophagus and the gastrointestinal tract followed the oral exposure. Owing to its low viscosity and low surface tension, white spirit poses a risk of aspiration into the lungs following oral exposure. A few mL of solvent aspirated into the lungs are able to produce serious bronchopneumonia and 10-30mL may be fatal.

Prolonged dermal exposure to white spirit, e.g., resulting from wearing clothes that have been soaked or moistened by white spirit for hours, may produce irritation and dermatitis.

Single cases of acute toxicity to the kidney, liver and bone marrow have been reported following exposure to white spirit at high levels. However, owing to lack of details and the sporadic nature of the reports, the relevance of these findings is unclear.

Inhalation of aliphatic hydrocarbon vapours seems to show little toxicity, but the vapours are CNS depressants and have a disinhibiting euphoric effect.

Potential Health Effects

Inhalation:

Short Term Exposure: Available data shows that this product is harmful, but symptoms are not available. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort and coughing.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

SAFETY DATA SHEET

Issued by: Lucas Oil Products of Australia Pty Ltd Phone: 07 3299 6320 (office hours)



Page: 5 of 6

This version issued: August, 2016

Short Term Exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is believed to be not irritating to eyes.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. Swallowing may result in nausea and vomiting. This product is unlikely to cause any irritation problems in the short or long term.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

Section 12 - Ecological Information

Insufficient data to be sure of status.

Biodegradation is expected to be the primary fate process for aliphatic hydrocarbons in soil and water. The rate and extent of biodegradation are dependent on the ambient temperature, the presence of a sufficient number of microorganisms capable of metabolizing the hydrocarbons and the concentration of white spirit in or on the soil or water.

Biodegradation of C_7 to C_{12} hydrocarbons is expected to be significant under environmental conditions favourable to microbial oxidation. Naturally occurring hydrocarbon-degrading microorganisms have been isolated from polluted soil and, to a lesser extent, non-polluted soil.

The low water solubility and moderate vapour pressure of white spirit (Stoddard solvent) suggest that volatilization and subsequent photo-oxidation are important processes for abiotic degradation in the atmosphere.

The octanol/water partition coefficient (log Pow) of white spirit (17% v/v aromatics) has been found to be 3.5 to 6.4. This indicates a moderate potential for bioaccumulation by organisms from water and a likelihood of partitioning to fat within organisms.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

Section 14 - Transport Information

UN Number: This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AICS

SWA

Australian Inventory of Chemical Substances

Safe Work Australia, formerly ASCC and NOHSC

CAS number

Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

SAFETY DATA SHEET

Issued by: Lucas Oil Products of Australia Pty Ltd Phone: 07 3299 6320 (office hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



Page: 6 of 6

This version issued: August, 2016

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)

Copyright © Kilford & Kilford Pty Ltd, August, 2016.

http://www.kilford.com.au/ Phone (02)9251 4532